

Smiota

Add-on Lockers
Indoor/Outdoor
Technical Specifications

More than just smart lockers.

Smiota add-on units can be installed indoors or outdoors and are compatible with any console unit.

These add-on units are available in full and half banks. Full banks consist of 4, 6, 8, 12, 14, 18, or 28 lockers. Half banks consist of 1, 2, or 6 lockers. All configurations can be connected to any console unit and are great for package drop-off and pick-up. All outdoor applications require a shelter to be installed on top.

Console units require a 110V (US) or 220V (UK/Europe) power supply. Add-on units connect to console units with an RS 485A cable.

To learn about Smiota Smart Locker use cases and applications, visit www.smiota.com.



Console with 12-door, full bank add-on

6960 Koll Center Pkwy Suite #305
Pleasanton, CA 94566

Tel: (925) 270-4321

Email: sales@smiota.com

Web: www.smiota.com



MODEL - INDOOR ADD-ON UNIT

SMS10-XXD, SMS11-XXD

MODEL - OUTDOOR ADD-ON UNIT

SMS00-XXD/SMS01-XXD

Dimensions and Construction

Color	Standard, Customizable
Standard Colors	RAL 7040  RAL 9018 
Weight (Pounds)	550 Pounds
Material	Cold Rolled Steel
Exterior Coating	Anti-corrosive Powder Coating
Interior Coating	Anti-corrosive Powder Coating
Thickness of the Steel	1.5 mm
Type of Construction	Welded Steel Construction
Coasters/Leveling Feet	Fixed Stand Off/Optional Coasters or Levelers
Type of Door	Hinged, Opens Left to Right and Vice Versa
Security	Lockable Doors
Customizable	Yes
Night Lamp with Weather Shelter	For Outdoor Only
External Weather Shelter	For Outdoor Only
Opaque/Transparent Doors	Both

Electrical System Configuration and Installation Features

Console Unit Power Supply (US)	110 V @ 15 amps Standard Supply
Console Unit Power Supply (UK/Eur)	220V @ 15 amps Standard Supply
Operating Temperature (Indoor)	40°F-70°F
Operating Temperature (Outdoor)	-20°F-120°F
Installation Location	Indoor or Outdoor
Sensors	IR Sensors, Door Lock
Door Mechanism	Auto-open, Manual Close
Components (UL-Approved)	Power Supply, Trip Switch, Cables

Connectivity

Connectivity	RS 485A
--------------	---------

Model

Available Models	1, 2, 4, 6, 8, 12, 14, 18, 28 Door Lockers
------------------	--

Application

Residential, Retail, Corporate, University
--

Locker Bank Dimensions

Full Bank	Height	Width	Depth
4 Door	78.35"	39.37"	25"
6 Door	78.35"	39.4"	25"
8 Door	78.35"	42.52"	25"
12 Door	78.35"	39.37"	25"
14 Door	78.35"	39.37"	25"
18 Door	78.35"	39.37"	25"
28 Door	78.35"	39.37"	25"
Half Bank	Height	Width	Depth
2 Door	78.35"	37.80"	25"
2 Door	78.35"	20"	23.03"
6 Door	78.35"	20"	25"

Locker Door Configurations

Full Bank

4 Door	4 Extra Large
6 Door	6 Large
8 Door	2 Medium, 6 Large
12 Door	4 Small, 4 Medium, 4 Large
14 Door	14 Medium
18 Door	12 Small, 4 Medium, 2 Large
28 Door	28 Small

Half Bank

1 Door	1 Extra Extra Large
2 Door	2 Extra Large
6 Door	2 Small, 2 Medium, 2 Large

Locker Door Dimensions

Size	Height	Width	Depth
S	4.33"	16.34"	25"
M	9.54"	16.34"	25"
L	20.28"	16.34"	25"
XL (4 Door)	35.33"	16.34"	25"
XL (6 Door)	35.33"	14.09"	25"
XXL	71.46"	31.89"	25"